













## Steam generators



### GV Katla

#### Standard equipment:

• 5.409.0256	
• 3.753.0111	
• 3.754.0228	
• 3.754.0229	
• 3.754.0235	
• 3.754.0250	
• 3.754.0230	
• 6.405.0240	
• 6.402.0096	
• 3.754.0234	
• 6.402.0095	
• 3.099.0126	

**Optional** • 5.409.0254 Steam gun with hose (10 m)

### GV Katla

- Saturated steam at 9 bar at a temperature of 175°C
- Steam gun with low tension control
- S. S. body AISI 304
- Boiler 3,3 kW S. S. AISI 304. Thickness 25/10
- Low level water lamp indicator
- Device for using chemicals and detergents mixed with steam
- Heating and activation time required: 7 min.
- Steam regulation
- Discharge valve
- Pressure gauge
- The boiler can be refilled from the tank provided (continuous duty)
- Wheels suitable for food and processing areas
- Storage basket.

GV Katla	
Code	8.453.0001
Absorbed power	3,3 Kw/230 V-Ph1
Max pressure	9 bar
Steam production	4,62 Kg/h
Max temperature	175° C
Water tank capacity	5 l.
Detergent tank capacity	5 l.



Watch the video on youtube:  
[www.youtube.com/fasavideo](http://www.youtube.com/fasavideo)

## Steam generators

Simple and intuitive control panel, quick-coupling steam gun, main ON/OFF switch with lamp, boiler ON/OFF switch with lamp, water/detergent selector, steam flow rate regulator, steam ready indicator lamp, low water level indicator lamp with buzzer, steam pressure gauge. Steam gun with integrated steam/detergent function activation key and quick coupling of accessories. Unlimited autonomy thanks to the continuous power supply of the boiler, which enables water top-ups in the tank without having to stop the machine or interrupt work, with major time saving in the operating phase. Boiler with saturated steam at 9 bar at a temperature of 175°C.

Equipped with 3 pumps: boiler, detergent and water. Maximum safety thanks to the 1 safety thermostat, 1 pressure switch and 1 mechanical maximum pressure valve. Discharge valve for complete discharge of the boiler; it eliminates water residues and formation of lime scale, thus lengthening the lifespan of the boiler. A 5-litre water and detergent double tank. A rich and complete range of accessories is supplied. Fieldswater and scale growth, extending boiler's life.



### Fields of applications

#### Steam system:

Food & beverage (food industry, catering, beverage, winery).

Hospitality, community & healthcare (hospitality, buildings cleaning, spa & sport, education & community, healthcare).

Industry (industry, transportation, car washers, car dealers).

