

## Maxima LP



**OPTIONAL** Hose reel with brake  
cod. 6.608.0010

### Standard equipment

- 6.601.0001 Gun PRO S'10 3/8" M with quick connection



- 6.602.0043 Lance 900 mm with quick connection.



- 3.103.0053 Nozzle type 060 (mod. 1515 LP)
- 3.103.0050 Nozzle type 045 (mod. 2015 LP)



- 4.618.0056 High pressure hose 20 m



- Power cable 5 m

## Maxima LP

- 4 poles electrical motor (1450 RPM) and thermal protection and water cooling
- Three ceramic pistons, brass linear pump head with built-in bypass valve
- Suction and delivery S/S valves.
- Automatic Stop System late shut down protection 24V
- Vertical burner with high thermal efficiency
- Header tank with antiscal tank
- Adjustable detergent delivery with built-in tank for direct suction (high-pressure delivery).
- Auxiliary motor for burner air-cooling and two ways fuel pump
- Glycerine pressure gauge
- Power cable (m 5)
- Temperature regulation gauge
- Gun with swivel hose fitting
- Low voltage control switches
- Tough steel main frame

### Optional:

- Hose-reel with brake without hose cod. 6.608.0010
- Antiscal LC-PRECAL (pcs. 4 x 5 lt.) cod. 3.697.0044

| Technical data:      | Maxima 1515 LP | Maxima 2015 LP |
|----------------------|----------------|----------------|
| Code                 | 8.622.0903     | 8.622.0904     |
| Operat. pressure bar | 30 ÷ 150       | 30 ÷ 200       |
| l/h                  | 450 ÷ 900      | 450 ÷ 900      |
| Max water temp.      | 140° C         | 140° C         |
| Power ass. kW        | 5,5            | 7,3            |
| RPM                  | 1450           | 1450           |
| Voltage              | 400V~50 Hz     | 400V~50 Hz     |