

## Sundek 5Y LP



Models:

Sundek5 55Y - 75Y



**OPTIONAL** Hose reel with brake  
cod. 6.608.0018

## Sundek 5 Y

- 4 poles electrical motor (1450 RPM) with thermal protection and water cooling (three phase models)
- Three ceramic coated pistons, brass linear pump head (Sundek 31Y), full ceramic pistons (Sundek 55Y - 75Y), brass linear pump head with built-in by-pass valve
- Vertical burner with high thermal efficiency steel coil.
- Suction and delivery S/S valves.
- Safety valve
- Temperature regulation gauge
- Glycerine pressure gauge.
- Automatic Stop System late shut down protection 24V.
- Adjustable detergent delivery with built-in tank for indirect suction.
- Auxiliary motor for burner air-cooling
- Two ways fuel pump
- Low fuel lamp
- Ergonomic handles and impact resistant covers
- Accessory holder
- Power cable (m 5).

### Optional:

- Hose-reel with brake. (6.608.0018)
- Antiscale LC-PRECAL (pcs. 4 x 5 lt.) cod. 3.697.0044

### Standard equipment

- 3.700.0030 Gun M22 - 3/8" (mod. 31 Y).



- 6.601.0001 Gun S'10 3/8" M with quick connection (mod. 55Y LP-75Y LP).



- 3.701.0015 Lance M22 high/low pres. (mod. 31Y LP)



- 6.602.0044 Lance 900 mm with quick connection. (mod. 55Y LP-75Y LP)



- 3.103.0050 Nozzle type 045 (mod. 31Y LP)
- 3.103.0053 Nozzle type 060 (mod. 55Y LP)
- 3.103.0050 Nozzle type 045 (mod. 75Y LP)



- 4.618.0143 H. P. hose 10 m



| Technical data:    | Sundek5 31Y | Sundek5 55Y | Sundek5 75Y |
|--------------------|-------------|-------------|-------------|
| Code               | 8.621.0948  | 8.621.0942  | 8.621.0943  |
| Operat. press. bar | 30 ÷ 110    | 30 ÷ 150    | 30 ÷ 200    |
| l/h                | 330 ÷ 660   | 450 ÷ 900   | 450 ÷ 900   |
| Max water temp.    | 140°C       | 140°C       | 140°C       |
| Power ass. kW      | 3           | 5,5         | 7,3         |
| RPM                | 1450        | 1450        | 1450        |
| Voltage            | 230 V~50 Hz | 400 V~50 Hz | 400 V~50 Hz |