

Cold water high-pressure cleaners

Tasman LP



Standard equipment:



3.700.0036 - mod. 1211 - 1509



3.700.0030 mod. 1713 - 2017



3.701.0027



3.103.0050 - mod. 1211
 3.103.0047 - mod. 1509
 3.103.0053 - mod. 1713
 3.103.0052 - mod. 2017



4.618.0049 - 8 m. mod. 1211 - 1509
 4.618.0143 - 10 m. mod. 1713 - 2017

Equipped with:

- 4 poles electrical motor (1450 RPM) with thermal protection and water cooling
- Three ceramic coated pistons, (full ceramic piston only for Tasman 1713) brass linear pump head with built-in by-pass valve.
- Suction and delivery S. S. valves.
- Low voltage and delayed Total Stop (three phase models)
- Detergent tank (2,8 lt.).
- Pressure regulator.
- Glycerine pressure gauge.
- Hose-reel (on request)

	Tasman 1211 LP	Tasman 1509 LP	Tasman 1713 LP	Tasman 2017 LP
Code	8.671.0009	8.671.0010	8.671.0011	8.671.0012
Operat. pressure bar	120 (max 150)	150 (max 160)	170	200
Operat. pressure psi	1740 (max 2175)	2175 (max 2320)	2465	2900
Delivery rate l/h	660	540	780	1000
Absorbed power W	3000	3000	6000	7500
RPM	1450	1450	1450	1450
Voltage	230V~50Hz	230V~50Hz	400V~50Hz	400V~50Hz